

XP-243B

Thermal Barcode Printer

Xprinter® 芯烨
XINYE

- Various label width, can be 20mm-60mm
- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing and Bluetooth



Coffee Shop



Shopping




Mart



XP-243B

Thermal Barcode Printer



MODEL	XP-243B	
Resolution	Thermal barcode	Thermal receipt
Printing width	203 dots/line	
Printing speed	56mm (Max)	48mm
Print head temperature sensor	Min 50.8mm/s, Max 101mm/s	90mm/s
Print head position sensor	Thermal sensitive resistance	
Media type	Micro switch	
Bar code	CODE128 / EAN128 / ITF / ITF25 / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14	UPC-A/UPC-E/JAN13 (EAN13)/ JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128
QR CODE	PDF417、QR CODE、Data Matrix	
Paper diameter	100mm(max)	
Paper off type	Tear off	
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation	
Gross weight	1.4 kg	
Dimension	206 x 136 x 148mm (D*W*H)	
Work	5~45°C, 20—80%RH	
Storage	-40~55°C, ≤93%RH(40°C)	
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux	
Input	DC12V, 3A	
Paper exists detection	Photoelectric sensor	
Interface	USB / USB+Bluetooth	
Memory	DRAM: 64K; FLASH: 4M	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
Http://www.poskeytech.com
Email: overseas@xprinter.net

