

XP-480B

Direct Thermal Barcode Printer



- High quality double-walled clamshell design
- 203 dpi and 300 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 4 MB Flash



XP-480B

Thermal Transfer/ Direct Thermal

BarTender®
BY SEAGULL SCIENTIFIC



MODEL	XP-480B
Printing Method	Direct Thermal
Resolution	8 dots/mm(203 DPI)
Interface	USB2.0 (Standard)/Serial(Optional)/Bluetooth(Optional)/WIFI(Optional)/SD(Optional)
Real Time Clock	Optional
Max Print Speed	127 mm (5") / s
Max Print Width	108mm (4.25")
Max Print Length	2286mm(90")
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	20 mm ~ 112 mm
Media Thickness	0.06 mm ~ 0.16 mm
Media Length	10 mm ~2286 mm
Label Roll Capacity	127 mm (5") external diameter
Ribbon	Max length: 90M; Max roll diameter: 35mm; Internal diameter: 0.5" (12.7mm); Ribbon width: 25.4mm-110mm (1"-4.3")
Memory	8MB Flash Memory 8MB SDRAM Micro SD card reader for Flash memory expansion, up to 4GB
Sensor	Gap sensor Printer Head opened sensor Black mark sensor Ribbon end sensor
Processor	32-bit RISC CPU
Power Supply	Input: AC 100-240V; Output: DC 24V/2.5A
Barcode	1D barcode: Code128 subsets A,B,C,Code128UCC, EAN128, Interleave 2 of 5, Code 39,Code 93, EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode: CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)
Emulation	TSPL-EZ (EPL, ZPL)
Dimension	240mm*211mm*166mm (W*H*D)
Weight	2.15 kg
Safety Standard	FCC, CE, CB, CCC
Environment	Operation condition: -10 ~ 50 °C (14 ~ 122 °F) ,10 ~ 90% non-condensing Storage condition : -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.poskeytech.com
Email: overseas@xprinter.net

