

Barcode Printer

XP-DT427B

Create For You



Product close up



Streamlined Industrial Design.



USB 2.0 Interface, High Speed Printer.

XP-DT427B is professional thermal direct label printer produced by Xprinter.

High performance and professional printing various type of labels, small and affordable.

Direct thermal label printer your best choice.

High Speed



High Quality



High performance



Product Features

- High quality double-walled clamshell design
- 203 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 8MB Flash

Application

- Express logistics industry
- Small office or home office mailings
- Shelf labeling
- Healthcare specimen labeling
- File-folder labeling
- Inventory and asset management

Direct Thermal Barcode Printer



Printer model	XP-DT427B
Resolution	8 dots/mm(203 DPI)
Printing method	Direct Thermal
Max. print speed	127 mm (5")/s
Max. print width	108 mm (4.25")
Max. print length	1778 mm (70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4~115mm
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Label length	10~1778mm(0.4" ~ 90")
Label roll capacity	127 mm (5") OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	210.8 mm (W) x 190.20 mm (H) x 180.2 mm (D)
Weight	1.40 kg
Processor	32-bit RISC CPU
Memory	8MB Flash Memory 8MB SDRAM SD card reader for Flash memory expansion, up to 4 GB
Interface	USB (Standard) Serial (Optional) WIFI (Optional) Bluetooth (Optional)
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue)
Sensors	Black mark reflective sensor (position adjustable) Head open sensor Transmissive gap sensor
Internal fonts	8 alpha-numeric bitmap fonts Windows fonts are downloadable from software.
Barcode	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code: CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)
Font and barcode rotation	0°、90°、180°、270°
Printer language	TSPL(EPL、ZPL、DPL)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC、CE、CCC、CB
Environmental concern	RoHS
Accessories	①Windows labeling software, driver and user manual CD ②quick start guide ③data cable ④power cord ⑤external switching power adapter ⑥label spindle, fixing tab x 2
Factory options	① Real time clock ② SD card slot
User options	① external roll mount (1"core) ② external roll mount board ③ Label case



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.poskeytech.com
Email: overseas@xprinter.net