

XP-C58A

Thermal Receipt Printer

Xprinter® 芯燁
XINYE

- High operational reliability
- Drop in paper loading with auto cutter
- Support Gb18030
- Supports a variety of international languages
- High print speed for both graphics and text



Coffee Shop



Shopping






Mart



XP-C58A

Thermal Receipt Printer



Model	XP-C58A
Printing method	Direct thermal
Printing speed	90mm/s
Printing width	57.5 ± 0.5mm
Paper diameter	60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13(EAN13) / JAN8(EAN8) / CODABAR/ITF/CODE39/ CODE93/CODE128
Code page	PC347 (Standard Europe) /Katakana、PC850 (Multilingual) / PC860 (Portuguese) /PC863 (Canadian-French) /PC865 (Nordic) / West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866 (Cyrillic#2) / PC852 (Latin2) /PC858/IranII/Latvian/Arabic/PT151 (1251) /024_PC747/ 025_[WPC1257]/027_[Vietnam]/028_PC864/029_PC1001/030_[Uigur]/ 031_[Hebrew]/032_WPC1255[Israel]/255_[Thai]
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V \approx 2.6A
Cash drawer control	DC 12V \approx 1A
Interface	USB/parallel/USB+Lan/USB+Bluetooth
Auto cutter	Partial
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 10/Linux
Command	Compatible with ESC/POS
Gross weight	0.5 kg
Dimension	169.3×122×113mm (D×W×H)



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
[Http://www.poskeytech.com](http://www.poskeytech.com)
Email: overseas@xprinter.net

