

## Direct thermal Printer




# XP-T58H

- Big gear printing head
- High speed, long life time, high quality
- Outstanding functions, Strong stability
- Compatible with ESC/POS commands



# XP-T58H

## Direct thermal Printer



| Model               | XP-T58H                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing method     | Direct thermal                                                                                                                                                                                                                                                                                                                                                                        |
| Printing speed      | 120mm/s                                                                                                                                                                                                                                                                                                                                                                               |
| Printing width      | 57.5 ± 0.5mm                                                                                                                                                                                                                                                                                                                                                                          |
| Paper diameter      | 65mm                                                                                                                                                                                                                                                                                                                                                                                  |
| Paper thickness     | 0.06~0.08mm                                                                                                                                                                                                                                                                                                                                                                           |
| Column capacity     | 384 dots/line                                                                                                                                                                                                                                                                                                                                                                         |
| Line space          | 3.75mm(changeable using commands)                                                                                                                                                                                                                                                                                                                                                     |
| Character size      | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24x24 dots                                                                                                                                                                                                                                                                                            |
| Bar code            | UPC-A/UPC-E/JAN13(EAN13) / JAN8(EAN8) / CODABAR/ITF/CODE39/<br>CODE93/CODE128                                                                                                                                                                                                                                                                                                         |
| Code page           | PC347(Standard Europe) / Katakana、PC850 (Multilingual) /<br>PC860(Portuguese) /PC863(Canadian-French) /PC865(Nordic) /<br>West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866(Cyrillic#2) /<br>PC852(Latin2) /PC858/IranII/Latvian/Arabic/PT151(1251) /024_PC747/<br>025_[WPC1257]/027_[Vietnam]/028_PC864/029_PC1001/030_[Uigur]/<br>031_[Hebrew]/032_WPC1255[Israel]/255_[Thai] |
| NV FLASH            | 64K Bytes                                                                                                                                                                                                                                                                                                                                                                             |
| Input buffer        | 32K Bytes                                                                                                                                                                                                                                                                                                                                                                             |
| Power supply        | DC 12V --- 2.6A                                                                                                                                                                                                                                                                                                                                                                       |
| Cash drawer control | DC 12V --- 1A                                                                                                                                                                                                                                                                                                                                                                         |
| Interface           | USB / Lan / Parallel / Serial                                                                                                                                                                                                                                                                                                                                                         |
| Reliability         | Printing head life: 50 km                                                                                                                                                                                                                                                                                                                                                             |
| Working environment | Temperature (0~45°C), humidity(10~80%)                                                                                                                                                                                                                                                                                                                                                |
| Storage environment | Temperature (-10~60°C), humidity(10~90%)                                                                                                                                                                                                                                                                                                                                              |
| Drivers             | Win XP/Win Vista/Win 7/Win 8/Win 10/Linux                                                                                                                                                                                                                                                                                                                                             |
| Command             | Compatible with ESC/POS                                                                                                                                                                                                                                                                                                                                                               |
| Gross weight        | 0.88 kg                                                                                                                                                                                                                                                                                                                                                                               |
| Dimension           | 182 × 135 × 119mm (D × W × H)                                                                                                                                                                                                                                                                                                                                                         |



Scan QR code to checkout Xprinter  
website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.poskeytech.com  
Email: overseas@xprinter.net

