

XP-T58K

Thermal Receipt Printer

POS Printer

Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Support Chinese GB18030
- Avoid order missing
- Compatible with ESC/POS commands



Specifications

| Model | XP-T58K |
|---------------------|--|
| Printing method | Direct thermal |
| Printing speed | 120mm/s |
| Paper width | 57.5 ± 0.5mm |
| Paper diameter | 60mm |
| Paper thickness | 0.06~0.08mm |
| Column capacity | 384 dots/line |
| Line space | 3.75mm (changeable using commands) |
| Character size | ANK, Font A: 12x24 dots Font B: 9x17 dots simplified/traditional Chinese: 24x24 dots |
| Bar code | UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 |
| Code page | PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251) |
| NV FLASH | 64K Bytes |
| Input buffer | 32K Bytes |
| Power supply | DC 12V = 2.6A |
| Cash drawer control | DC 12V = 1A |
| Interface | Parallel/Serial/USB/Lan/Bluetooth+USB |
| Auto cutter | --- |
| Reliability | Printing head life: 50 km |
| Working environment | Temperature (0~45°C), humidity(10~80%) |
| Storage environment | Temperature (-10~60°C), humidity(10~90%) |
| Drivers | Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux |
| Command | Compatible with ESC/POS |
| Gross weight | 1.10 kg |
| Dimension | 199 x 132 x 111.5mm D(W x H) |