

TRANSPORT

To provide you with the best transport solution



Xprinter® 芯烨
XINYE



XP-80mm Series printer XP-P800

XP-P800 is an excellent performance mobile printer. It's with 2000mAh lithium Ion battery, and is widely used in police, tobacco, postal, transportation, distribution and other fields

Product highlights

- High quality printing
- Easy paper loading
- 80mm paper width
- Easy to operate
- Portable
- Support GB18030



Android



iOS 8



Windows 7



Windows 8



Windows 10



Linux

XP-P800 Mobile Printer

■ Feature

Fashionable appearance

Fashionable appearance, contracted style



Easy to operate

Simple, easy to operate panel design



Easy paper loading

Quick and easy drop paper design.



■ Specification



MODEL	XP-P800
Printing method	Direct thermal
Printing speed	50mm/s
Paper width	79.5 ± 0.5mm
Paper roll diameter	≤40mm
Paper thickness	0.06~0.08mm
Character per line	576 dots/line
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Interface	Bluetooth+USB+Serial
Bar code	1D Barcode: UPC-A/UPC-E/JAN13 (EAN13) / JAN8 (EAN8) / CODABAR/ITF/CODE39/CODE93/CODE128 2D Barcode: QR CODE/PDF417
Extended characters	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、 PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、 West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、 PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、 Arabic、PT151 (1251)
NV FLASH	64 K Bytes
Input buffer	32 K Bytes
Power supply	Input: AC 110V/240V, 50~60Hz
Power	Output: AC 9V-2A
Battery	2000mAh
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45℃), humidity(10~80%)
Storage environment	Temperature (-10~60℃), humidity(10~90%)
Operating system	Win 9X/Win 2000/Win 2003/Win XP/Win 7/Win 8/Win 10/Linux/IOS/Android
Gross weight	0.21 kg
Dimension	108.5×105×48mm (L×W×H)



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
[Http://www.poskeytech.com](http://www.poskeytech.com)
Email: overseas@xprinter.net

