

# XP-237B

## Thermal Barcode Printer

- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing

# Xprinter®



Coffee Shop



Shopping




Mart



# XP-237B

## Thermal Barcode Printer



| MODEL                      | XP-237B  |
|----------------------------|--|
| Resolution                 | Thermal barcode  |
| Printing width             | 56mm (Max)   |
| Printing speed             | Min 50.8mm/s, Max 101mm/s  |
| Print head position sensor | Thermal sensitive resistance   |
| Media type                 | Micro switch   |
| Bar code                   | CODE128 / EAN128 / ITF / ITF25 /<br>CODE39 / CODE39C / CODE39S / CODE93 /<br>EAN13 / EAN13+2 / EAN13+5 / EAN8 /<br>EAN8+2 / EAN8+5 / CODABAR / POSTNET /<br>UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 /<br>UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14 |
| QR CODE                    | PDF417、QR CODE、Data Matrix   |
| Paper diameter             | 100mm(max)   |
| Paper off type             | Tear off   |
| Internal font              | FONT 0 to FONT 8; Commonly used in single-byte fonts   |
| Enlargement & rotation     | 1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation   |
| Gross weight               | 1.18 kg  |
| Dimension                  | 210 x 136 x 156mm (D*W*H)  |
| Work                       | 5~45°C, 20—80%RH   |
| Storage                    | -40~55°C, ≤93%RH(40°C)   |
| Drivers                    | Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux   |
| Input                      | DC12V, 3A  |
| Paper exists detection     | Photoelectric sensor   |
| Interface                  | USB / USB+Bluetooth  |
| Memory                     | DRAM: 64K; FLASH: 4M   |
| Image                      | Monochromatic PCX, BMP image files can be load to FLASH, DRAM  |



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.poskeytech.com  
Email: overseas@xprinter.net

