

XP-5811K

Thermal Receipt Printer

Xprinter®

- High operational reliability
- Drop in paper loading
- Support QR code
- Supports a variety of international languages
- High print speed for both graphics and text



Coffee Shop



Shopping




Mart



XP-58IIK

Thermal Receipt Printer



Model	XP-58IIK
Printing method	Direct thermal
Printing speed	90mm/s
Printing width	48mm
Paper width	57.5 ± 0.5mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、 PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、 West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、 PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、 Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6 A
Cash drawer control	DC 12V = 1A
Power adapter	AC 110V/220V, 50~60Hz
Interface	USB+Serial+Bluetooth
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 10/Linux
Command	Compatible with ESC/POS
Gross weight	0.498 kg
Dimension	120×110×112.7mm (D×W×H)



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
[Http://www.poskeytech.com](http://www.poskeytech.com)
Email: overseas@xprinter.net

