

M811

Thermal Receipt Printer



Key features

- Set up printer by web page directly.
- Printer status monitoring
- Input buffer 2048K bytes
- Support QR code printing
- Support Linux& Windows operating system

APPLICATIONS



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

M811

Thermal Receipt Printer



MODEL	M811	
Printing method	Direct thermal	
Printing width	72mm	
Printing speed	230 mm/s	300mm/s
Interface	USB+LAN / USB+Serial	USB+Serial+Lan
Column capacity	576 dots/line 512 dots/line	
Paper Width	79.5±0.5mm	
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)	
Image	Monochrome BMP image files can be load to FLASH	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128	
2-dimension code	QR Code, PDF 417(available for 3 ports)	
Input buffer	64k bytes	2048 K bytes
NV Flash	256k bytes	
Power adaptor	Input: AC 110V/220V, 50~60Hz	
Power source	Output: DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Weight	1.65 KG	
Dimensions	188×145×148mm (D×W×H)	
Work environment	Temperature (0~45℃) humidity(10~80%)	
Storage environment	Temperature(-10~60℃) humidity(10~80%)	
Driver	Windows/Linux	
Emulation	ESC/POS	
Auto cutter	Partial	
Cutter life	1.5 million cuts	
Printer head life	100KM	

