

M800

Thermal Receipt Printer

- Fast and versatile printing up to 300mm per second
- Space saving design
- Drop in paper loading and with auto Cutter



Coffee Shop



Shopping




Mart



M800

Thermal Receipt Printer



MODEL	M800	
Printing method	Direct thermal	
Printing speed	230mm/s	300mm/s
Interface type	USB+Serial / USB+Lan	USB+Serial+Lan
Paper width	79.5±0.5mm	
Printable area	72mm	
Maximum paper diameter	Φ80 mm	
Paper thickness	0.06~0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm(Changeable by commands)	
Commands	Compatible with ESC/POS	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Dimension	200×145×137mm (D×W×H)	
Gross weight	1.56 kg	
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2-dimension code	QR CODE / PDF417	
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)	
Cutter	Partial	
Cutter life	1.5 million cuts	
Print head life	100KM	
Input buffer	128 K bytes	2048 K bytes
NV Flash	256 K bytes	
Power adaptor	AC110V/220V, 50~60Hz	
Power source	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Work environment	Temperature: 0~45°C, humidity: 10~80RH%	
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%	
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux	

