



XP-350BM/350B

Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 80mm label diameter, external amount and board option
- Thermal sensitive resistance, photoelectric sensor black mark sensor
- USB+Serial+ethernet all in one interface

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing



Express



Factory

XP-350BM / 350B

Desktop Barcode Printer



BARCODE




PEELER



VARIOUS INTERFACE



EASY LOAD



COMPACT DESIGN



HIGH SPEED

MODEL	XP-350BM	XP-350B
Printing method	Direct thermal	
Resolution	203dpi (8dots/mm)	
Paper width	16~82mm	
Paper thickness	0.06~0.19mm	
Printing speed	Min: 50.8mm/s Max: 152mm/s	
Print head temperature sensor	Thermal sensitive resistance	
Paper diameter	100mm(MAX), Support External paper roll holder(Optional)	
Bar Codes	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14 PDF417、QR CODE、Data Matrix	
Print head position sensor	Micro switch	
Media type	Label, Sticker, Continuous, gap, black mark, fan-fold and punched hole	
Paper off type	Tear off & peel off	Tear off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation	
Gross weight	1.44 kg	
Dimension	220(D) x 148(W) x 150(H)mm	
Work enviroment	5~45°C, 20~80%RH	
Storage enviroment	-40~55°C, ≤93%RH(40°C)	
Drivers	Win XP/Win 7/Win 8/Win 10/Android/IOS	
Input	24VDC, 2.5A	
Paper exists detection	Photoeletric sensor	
Interface	Serial+USB+Lan	USB+Serial
Memory	DRAM: 4M; FLASH: 4M	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net



Windows 7



Windows 8



Windows 10

