# Xprinter® 芯烨
XINYE

# XP-P300 Mobile Receipt Printer

Xprinter XP-P300 is a 2-inch-wide mobile receipt printer, it is with clam shell design for easy media loading, easy to carry and simple to use, the XP-P300 is lightweight enough to fit in a pocket or wear comfortable on a belt. With cash drawer interface, also can print on desktop computer. Quickly print and tear receipt, widely used in tickets and delivery notices on site, save time and money, improving customer service, XP-P300 is your best choice.

Rechargeable

## ☼ Features

- Clam shell design for easy media loading
- Cash drawer interface supported
- ESC/POS programming language
- Four LEDS as User Interface indicators
- Paper run out alarm sensor
- Android, Apple IOS mobile connectivity
- 7.4V Li-ion, 2000mAh battery; rechargeable
- 7 days standby time, designed with "sleep mode" to conserve battery

## ☼ Support

Avoid order missing

ANDROID

High printing speed

OPOS
Support OPOS driver

Support network printing

10
iOS 10

Retail    Hospitality    Healthcare    Transportation    Manufacturing

Rechargeable — Cash drawer interface — Power

Android  IOS10  Linux  Windows 7  Windows 8  Windows 10

## Specifications

| MODEL | XP-P300 |
|---|---|
| Printing method | Direct thermal |
| Printing speed | 70mm/s |
| Paper width | 58mm |
| Paper roll diameter | ≤50mm |
| Paper thickness | 0.06~0.08mm |
| Resolution | 8 dots (203dpi) |
| Character size | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24x24 dots |
| Character per line | 384 dots/line |
| Interface | USB+Bluetooth |
| Bar code | UPC-A/UPC-E/JAN13（EAN13）/JAN8（EAN8）/CODABAR/ITF/<br>CODE39/CODE93/CODE128/PDF417/ QR code |
| Extended characters | PC347（Standard Europe）/ Katakana / PC850（Multilingual）/ PC860（Portuguese）/<br>PC863（Canadian-French）/ PC865（Nordic）West Europe / Greek / Hebrew /<br>East Europe / Iran / WPC1252 / PC866（Cyrillic#2）/ PC852（Latin2）/ PC858 / IranII /<br>Latvian / Arabic / PT151（1251） |
| NV FLASH | 64 K Bytes |
| Input buffer | 32 K Bytes |
| Power supply | Input：AC 110V/240V, 50～60Hz    Output: DC 9V/2A |
| Battery | 7.4V/2000m Ah |
| Reliability | Printing head life: 50 km |
| Working environment | Temperature (0~45°c), humidity(10~80%) |
| Storage environment | Temperature (-10~60°c), humidity(10~90%) |
| Operating environment | Win 2000/Win 2003/Win XP/Win 7/Win 8/Win 10/Linux/ IOS / Android |
| Print command | Compatible with ESC/POS |
| Gross weight | 0.213 kg (Exclude paper roll and battery) |
| Dimension | 150 × 80 × 58mm (D × W × H) |