

Xprinter®

Barcode Printer

XP-DT427B

Create For You



■ Product close up



Streamlined Industrial Design.



USB 2.0 Interface, High Speed Printer.

XP-DT427B is professional thermal direct label printer produced by Xprinter.

High performance and professional printing various type of labels, small and affordable.

Direct thermal label printer your best choice.

■ Product Features

- High quality double-walled clamshell design
- 203 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 8MB Flash

■ Application

- Express logistics industry
- Small office or home office mailings
- Shelf labeling
- Healthcare specimen labeling
- File-folder labeling
- Inventory and asset management

High Speed



High Quality



High performance



Direct Thermal Barcode Printer

Specifications

Printer model	XP-DT427B
Resolution	8 dots/mm(203 DPI)
Printing method	Direct Thermal
Max. print speed	127 mm (5")/s
Max. print width	108 mm (4.25")
Max. print length	1778 mm (70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4~115mm
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Label length	10~1778mm(0.4" ~ 90")
Label roll capacity	127 mm (5") OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	210.8 mm (W) x 190.20 mm (H) x 180.2 mm (D)
Weight	1.40 kg
Processor	32-bit RISC CPU
Memory	8MB Flash Memory 8MB SDRAM SD card reader for Flash memory expansion, up to 4 GB
Interface	USB (Standard) Serial (Optional) WIFI (Optional) Bluetooth (Optional)
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue)
Sensors	Black mark reflective sensor (position adjustable) Head open sensor Transmissive gap sensor
Internal fonts	8 alpha-numeric bitmap fonts Windows fonts are downloadable from software.
Barcode	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code: CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)
Font and barcode rotation	0°、90°、180°、270°
Printer language	TSPL(EPL、ZPL、DPL)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC、CE、CCC、CB
Environmental concern	RoHS
Accessories	①Windows labeling software, driver and user manual CD ②quick start guide ③data cable ④power cord ⑤external switching power adapter ⑥label spindle, fixing tab x 2
Factory options	① Real time clock ② SD card slot
User options	① external roll mount (1"core) ② external roll mount board ③ Label case



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

