



Xprinter® 芯烨
XINYE

Direct thermal Printer

XP-58IIQ




- Big gear printing head
- High speed, long life time, high quality
- Outstanding functions, Strong stability
- Compatible with ESC/POS commands



XP-58IIQ

Direct thermal Printer



Model	XP-58IIQ
Printing method	Direct thermal
Printing speed	90mm/s
Printing width	48mm
Paper diameter	58mm / 60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13(EAN13) / JAN8(EAN8) / CODABAR/ITF/CODE39/ CODE93/CODE128
Code page	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V $\pm$ 2.6A
Cash drawer control	DC 12V $\pm$ 1A
Interface	USB / USB+Bluetooth / USB+Lan
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 10/Linux
Command	Compatible with ESC/POS
Gross weight	0.412 kg
Dimension	148 × 108 × 115mm (D × W × H)



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprinter.com
Email: overseas@xprinter.net

