



Thermal Receipt Printer

XP-E200M / E260M / E300M

- Reprinting function
- Queue printing function
- Page mode printing
- Cutter Jam Auto-Elimination
- 2-inch & 3-inch receipt supported



XP-E200M / E260M / E300M

Thermal Receipt Printer



MODEL	XP-E200M	XP-E260M	XP-E300M
Printing method	Direct thermal		
Printing speed	200 mm/s	260 mm/s	300 mm/s
Paper width	58mm / 80mm		
Printable area	72mm(adjustable by commands)		
Maximum paper diameter	Φ80mm		
Paper thickness	0.06-0.08mm		
Column capacity	576 dots/line 512 dots/line		
Line space	3.75mm(Changeable by commands)		
Commands	Compatible with ESC/POS		
Interface type	USB / USB+Serial	USB / USB+Serial	USB+Serial+Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots		
Dimension	178 x 140 x 128mm (D×W×H)		
Gross weight	1.16 kg		
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128		
2-dimension code	QR CODE / PDF417		
Code page	PC437(Std.Europe) / (Katakana)\n\ / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / (West Europe) / (Greek) / (Hebrew) / (East Europe) / (Iran) / (WPC1252) / PC866(Cyrillic#2) / PC852(Latin2) / (PC858) / (IranII) / (Latvian) / (Arabic) / (PT1511251)		
Cutter	Partial		
Cutter life	1.5 million cuts		
Print head life	100KM		
Input buffer	64 Kbytes		2048 Kbytes
NV Flash	256 Kbytes		
Power adaptor	AC110V/220V, 50~60Hz		
Power source	DC 24V/2.5A		
Input voltage	DC 24V/2.5A		
Cash drawer output	DC 24V/1A		
Work environment	Temperature: 0~45°C, humidity: 10~80RH%		
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%		
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux		



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

