

XP-58IIK

Thermal Receipt Printer

Xprinter®

- High operational reliability
- Drop in paper loading
- Support QR code
- Supports a variety of international languages
- High print speed for both graphics and text



Coffee Shop



Shopping




Mart



XP-58IIK

Thermal Receipt Printer



Model	XP-58IIK
Printing method	Direct thermal
Printing speed	90mm/s
Printing width	48mm
Paper width	57.5 ± 0.5mm
Paper roll diameter	60mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 QR CODE
Code page	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6 A
Cash drawer control	DC 12V = 1A
Power adapter	AC 110V/220V, 50~60Hz
Interface	USB / USB+Serial / USB+Bluebooth / USB+Bluebooth+Serial / USB+Bluebooth+Serial+WiFi
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 10/Linux
Command	Compatible with ESC/POS
Gross weight	0.498 kg
Dimension	120×110×112.7mm (D×W×H)



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprinter.com
Email: overseas@xprinter.net

