

XP-DT325B

3" Direct Thermal Barcode printer

- Printing speed up to 127 mm (5") / s
- 8MB Flash Memory, 8MB SDRAM/MicroSD
- Employs a user-friendly double-wall clamshell design
- Built-in adaptor
- Head-up sensor / Gap sensor / Black mark sensor

Xprinter®



Coffee Shop



Shopping




Mart



XP-DT325B

3" Direct Thermal Barcode printer



MODEL	XP-DT325B		
Printing method	Direct thermal		
Resolution	200dpi		
Printing width	80mm (3.15")		
Paper roll diameter	25.4 ~ 76.2 mm (1" ~ 3")		
Printing length (Max.)	1778 mm (70")		
Paper thickness	0.06 ~ 0.20 mm (1.5 ~ 5.08 mil)		
Printing speed	127 mm (5") / s		
Print head temperature sensor	Thermal sensitive resistance		
Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST		
2D bar code	PDF-417, Maxicode, DataMatrix, QR code		
Print head position sensor	Micro switch		
Media type	Label, Sticker, Continuous, gap, black mark, fan-fold and punched hole		
Paper off type	Tear off		
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts		
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation		
Gross weight	1.1 kg		
Dimension	187(D) x 162(W) x 146(H)mm		
Work enviroment	5~40°C, 25~85%RH		
Storage enviroment	-40~55°C, ≤93%RH(40°C)		
Drivers	Win XP/Win 7/Win 8/Win 10/Android/IOS		
Memory	DRAM: 8M; FLASH: 8M		
Paper exists detection	Photoeletric sensor		
Interface	USB	Bluetooth (Optional)	WIFI (Optional)
Emulation	TSPL、EPL、ZPL、DPL		
Power adaptor	AC110V/220V, 50~60Hz		
Power source	DC 24V/2.5A		
Cash drawer output	DC 24V/1A		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

