

Thermal Receipt Printer


XP-D230H / D300H

- Front paper exit, Pagemode available
- High printing speed up to 300mm per second
- Sound and light alarm function available
- Support printer states monitor function



XP-D230H / D300H

Thermal Receipt Printer



MODEL	XP-D230H	XP-D300H
Printing method	Direct thermal	
Printing speed	230mm/s	300mm/s
Paper width	79.5±0.5 mm	
Printable area	72mm(adjustable by commands)	
Maximum paper diameter	Φ80 mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm(Changeable by commands)	
Commands	Compatible with ESC/POS	
Interface type	USB / Lan	USB+Serial+Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Dimension	185×140×134mm (D×W×H)	
Gross weight	1.84 kg	
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2-dimension code	QR CODE / PDF417	
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)	
Cutter	Partial	
Cutter life	1.5 million cuts	
Print head life	100KM	
Input buffer	64 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	
Power adaptor	AC110V/220V, 50~60Hz	
Power source	DC 24V/2.5A	
Input voltage	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Work environment	Temperature: 0~45℃, humidity: 10~80RH%	
Storage environment	Temperature: -10~60℃, humidity: 10~90RH%	
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net



Windows 7



Windows 8



Windows 10

