

XP-236B

Thermal Barcode Printer

- Adjustable print speed: Min 50.8mm/s, Max 101mm/s
- Adjustable paper width: Min 20mm, Max 60mm
- Maximum paper roll diameter: 80mm
- Support QR CODE Printing

Xprinter®



Coffee Shop



Shopping





Mart



XP-236B

Thermal Barcode Printer



MODEL	XP-236B	
Printing method	Thermal label mode	Thermal receipt mode
Resolution	203dpi	384 dots / line
Paper width	20 mm ~ 60 mm	58mm
Printing width	56mm	48mm
Printing speed	50.8mm/s, Max:101mm/s	90mm/s
Max. Media Diameter	80mm	
Max print length	100mm	
Bar Codes	CODE128/EAN128/ITF/CODE39/CODE39C/CODE 39S/CODE93/ EAN13/EAN13+2/EAN13+5/EAN8/ EAN8+2/EAN8+5/CODABAR/POSTNET/UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5/MSI/MSIC/PLESSEY/ ITF14/EAN14	UPC-A/UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/ CODABAR/ CODE93/CODE128
	QR CODE	QR CODE
Memory	DRAM:64K; FLASH:4M	
Paper off type	Tear off	
Print head temperature sensor	Thermal sensitive resistance	
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese,traditional Chinese:3.0×3.0mm(24×24 dots)
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270° rotation	
Gross weight	1.08 kg	
Dimension	189*130*133 mm	
Work enviroment	5~45℃, 20~80%RH	
Storage enviroment	-40~55℃, ≤93%RH(40℃)	
Drivers	Win XP/Win 7/Win 8/Win 10/Android/IOS	
Input	DC 9V / 3A	
Interface	USB/USB+BT/USB+WiFi	USB/USB+BT/USB+WiFi
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

