

# XP-D300M

## Thermal Receipt Printer

Xprinter®

- Easy Maintenance: Support update firmware online easy drop-in paper loading
- User can search and manage Lan printer directly by software
- Fast printing speed up to 300mm/s
- Support placed vertically or horizontally



Restaurant



Shopping




Mart



Wall-hanging

# XP-D300M

## Thermal Receipt Printer



|                                   |                                                                                                                                                                                                                                                                                 |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                      | <b>XP-D300M</b>                                                                                                                                                                                                                                                                 |
| <b>Printing method</b>            | Direct thermal                                                                                                                                                                                                                                                                  |
| <b>Paper width</b>                | 79.5±0.5mm □80mm                                                                                                                                                                                                                                                                |
| <b>Print width</b>                | 72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm                                                                                                                                                                                                                                              |
| <b>Column capacity</b>            | 576 dots/line(adjustable by command)                                                                                                                                                                                                                                            |
| <b>Printing speed</b>             | 300 mm/s Max.                                                                                                                                                                                                                                                                   |
| <b>Interface</b>                  | USB+Serial+Lan                                                                                                                                                                                                                                                                  |
| <b>Line spacing</b>               | 3.75mm (Adjustable by commands)                                                                                                                                                                                                                                                 |
| <b>Column number</b>              | 80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/<br>Chinese, traditional Chinese - 21 columns or 24 columns                                                                                                                                     |
| <b>Character size</b>             | ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots)<br>Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)                                                                                                                                                           |
| <b>Cutter</b>                     |                                                                                                                                                                                                                                                                                 |
| <b>Auto cutter</b>                | Partial                                                                                                                                                                                                                                                                         |
| <b>Barcode Character</b>          |                                                                                                                                                                                                                                                                                 |
| <b>Extension character sheet</b>  | PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) /<br>PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew /<br>East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII /<br>Latvian / Arabic / PT151(1251) |
| <b>Barcode types</b>              | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128                                                                                                                                                                                                           |
| <b>2D Barcode</b>                 | QR CODE / PDF417                                                                                                                                                                                                                                                                |
| <b>Input buffer</b>               | 2048 Kbytes                                                                                                                                                                                                                                                                     |
| <b>NVFlash</b>                    | 256 Kbytes                                                                                                                                                                                                                                                                      |
| <b>Power</b>                      |                                                                                                                                                                                                                                                                                 |
| <b>Power adaptor</b>              | Input: AC 100-240V, 50 ~ 60Hz Output: DC 24V/2.5A                                                                                                                                                                                                                               |
| <b>Printer input</b>              | DC 24V/2.5A                                                                                                                                                                                                                                                                     |
| <b>Cash drawer output</b>         | DC 24V/1A                                                                                                                                                                                                                                                                       |
| <b>Physical characteristics</b>   |                                                                                                                                                                                                                                                                                 |
| <b>Weight</b>                     | 1.44 Kg                                                                                                                                                                                                                                                                         |
| <b>Dimensions</b>                 | 144.5×146×188.5mm ( D×W×H)                                                                                                                                                                                                                                                      |
| <b>Environmental Requirements</b> |                                                                                                                                                                                                                                                                                 |
| <b>Work environment</b>           | Temperature (0 ~ 45℃) humidity(10 ~ 80%)                                                                                                                                                                                                                                        |
| <b>Storage environment</b>        | Temperature(-10 ~ 60℃) humidity(10 ~ 80%)                                                                                                                                                                                                                                       |
| <b>Reliability</b>                |                                                                                                                                                                                                                                                                                 |
| <b>Cutter life</b>                | 1.5 million cuts                                                                                                                                                                                                                                                                |
| <b>Printer head life</b>          | 150 KM                                                                                                                                                                                                                                                                          |
| <b>Software</b>                   |                                                                                                                                                                                                                                                                                 |
| <b>Emulation</b>                  | ESC/POS                                                                                                                                                                                                                                                                         |
| <b>Driver</b>                     | Windows/JPOS/OPOS/Linux/Android/Mac                                                                                                                                                                                                                                             |
| <b>Utility</b>                    | Windows & Linux test Utility                                                                                                                                                                                                                                                    |
| <b>SDK</b>                        | iOS/ Android/ Windows                                                                                                                                                                                                                                                           |



Scan QR code to checkout Xprinter  
website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

