



Xprinter® 芯燁
XINYE

Thermal Receipt Printer


XP-C2008

- Water proof, oil proof , dust proof design
- Fast and versatile printing up to 300mm per second
- Wifi, Bluetooth option
- Drop in paper loading and with auto cutter



XP-C2008

Thermal Receipt Printer



Model	XP-C2008	
Printing method	Direct thermal	
Printing paper	79.5±0.5mm×φ80mm	
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	300 mm/s Max.	
Interface	USB+Serial+Lan/USB+Parallel (Optional : WIFI/Bluetooth)	
Line spacing	3.75mm (Adjustable by commands)	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
Cutter		
Auto cutter	Partial	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	2048 Kbytes	
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	1.70 Kg	
Dimensions	190×145×150mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)	
Reliability		
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/Android/Windows	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

