

XP-T260L

Thermal Receipt Printer

Xprinter®



Support OPoS driver



Android



iOS 11

FEATURES

- 300mm/s printing speed
- USB+3USB HUB+LAN interface
- Support up to three USB devices connection (Maximum operating power 5V, 500mA for each connection), such as Desktop scanner, USB scanner, MSR magnetic card strip reader with USB, keyboard, Bluetooth USB dongle etc.
- Set up printer by web page directly.
- Printer status monitoring
- Input buffer 2048K bytes
- Support QR code printing
- Support Linux& Windows operating system

APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant




Ticketing



Parking

XP-T260L

Thermal Receipt Printer



Model	XP-T260L	
Printing method	Direct thermal	
Printing paper	79.5±0.5mm	
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	300 mm/s Max.	
Interface	USB+3USB HUB+LAN	
Line spacing	3.75mm （Adjustable by commands）	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
Cutter		
Auto cutter	Partial	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	2048 Kbytes	
NVFlash	256 Kbytes	
Power		
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	1.65 KG	
Dimensions	188×145×148mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)	
Reliability		
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/Android/Windows	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

