

XP-58IIK

Direct thermal Printer



Key features

- Outstanding functions, Strong stability
- Support main stream systems
- Support OPOS driver
- Avoid order missing
- Support simplified/traditional Chinese, Japanese,
- Korean and many other international languages

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-58IIK

Direct thermal Printer



Model	XP-58IIK
Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Printing speed	90 mm/s Max.
Interface	USB / Lan / Serial / Parallel
Line spacing	3.75mm (Adjustable by commands)
Fonts Symbology	
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Barcode	QR code
Input buffer	32 Kbytes / 64 Kbytes
NV Flash	64 Kbytes
Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A
Power source	DC 12V/2.6A
Cash drawer	DC 12V/1A
Physical characteristics	
Weight	0.73 kg
Dimensions	180*132*112 mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability	
Printer head life	50 KM
Software	
Emulation	ESC/POS
Driver	Windows/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/ Android/ Windows



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
 Email: overseas@xprinter.net

