

XP-243B

Thermal Barcode Printer

- Various label width, can be 20mm-60mm
- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing and Bluetooth

Xprinter®



Coffee Shop



Shopping




Mart



XP-243B

Thermal Barcode Printer



Model		XP-243B	
Mode	Label print mode		Receipt print mode
Printing Features			
Resolution	203 DPI		
Printing method	Direct Thermal		
Max.print speed	50.8~101 mm/s Max.		90 mm/s Max.
Max.print width	56 mm		48mm
Max.print length	Max. 1000 mm		/
Media			
Media type	Paper End, Cover Open, Gap		Paper End, Cover Open
Media width	20~60 mm		58mm
Media thickness	0.06 ~ 0.08 mm		
Media roll diameter	Max.100 mm		
Supply method	Easy Paper Loading		
Performance Features			
Input buffer	4096 Kbytes		4096 Kbytes
NV flash	4096 Kbytes		4096 Kbytes
Interfaces	USB/USB+Serial/USB+Bluetooth		
Sensors	Paper End, Cover Open, Gap		Paper End, Cover Open
Drawer port	1 ports (Pin 2 for cashdrawer)		
Fonts/Graphics/Symbologies			
Character sizes	Font 0 to Font8		Font A: 12x24, Font B: 9x17, CHN: 24*24
1D barcode	CODE128, EAN128, ITF, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14		Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D bar code	QR code		QR code
Emulaion	TSPL		ESC/POS
Physical Features			
Dimension	206×136×148 mm (D×W×H)		
Weight	1.08 kg		
Reliability			
Print head life	50 km		
Software			
Driver	Windows		Windows, Linux, Mac, Android
SDK	iOS/ Android/ Windows		
Power supply			
Input	100-240V 50/60H		
Output	DC 12V/3A		
Environmental Conditions			
Operation	0~45 °C Humidity: RH 10 ~ 80%		
Storage environment	-10 ~ 60°C Humidity: 10 ~ 90%		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

