

Xprinter®

Impact Dot matrix Printer




XP-D76EC

- Support Chinese GB18030
- Transfer simplified/traditional Chinese by using commands
- Avoid order missing
- Black mark orientation
- Imported Citizen DP332 printing head



XP-D76EC

Impact Dot matrix Printer



Model	XP-D76EC
Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5mm
Print Resolution	72 dpi (Horizontal)/ 144 dpi (Vertical)
Printing speed	4.5 line/s Max.
Interface	Serial+USB+Lan
Printing paper	75.5±0.5mm×φ80mm(max)
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	Font A - 33 columns / Font B - 40 columns / Chinese, traditional Chinese - 22 columns
Character	
Extension character sheet	PC437/Katakana/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858
Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Cutter	
Auto cutter	Partial
Software	
Driver	Windows / Linux / Mac
Utility	Windows
SDK	Windows / Android
Physical characteristics	
Weight	2.2 KG
Dimensions	247×156×143mm (D×W×H)
Environmental Requirements	
Work environment	0 ~ 45°C, 10 ~ 80% RH
Storage environment	-10 ~ 60°C, 10 ~ 90% RH (no condensation)
Reliability	
Cutter lif	1 million cuts
Printer head life	10 Million Lines



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

