

Mobile Receipt printer

XP-P200



Key features

- Easy paper loading structure design
- High speed printing
- Easy operate
- 7 days standby time
- Portable

Applications



Shopping



Mart



Restaurant



Hospital





Coffee Shop



Ticketing

XP-P200

Mobile receipt printer



Printing	
Printing method	Direct thermal
Printing width	48mm
Paper width	58mm
Paper roll diameter	≤30mm
Resolution	203 dpi
Printing speed	80 mm/s
Interface	USB+Serial+Bluetooth
Line spacing	3.75mm (changeable using commands)
Character size	ANK, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese, traditional Chinese: 3.0×3.0mm(24×24 dots)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns

Barcode Character	
Extended character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII / Latvian/ Arabic/ PT151(1251)
Barcode types	1D: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D: QR CODE / PDF417

Buffer	
Input buffer	32k bytes
NV Flash	64k bytes

Power	
Power supply	AC 110V/240V, 50~60Hz
Power source	Output: DC 9V-2A

Reliability	
Print head life	50 KM

Physical characteristics	
Gross weight	0.22 kg
Dimensions	111×88×41mm(D x W x H)

Environmental Conditions	
Work environment	0~45°C, 10~80% RH
Storage environment	-10~60°C, 10~90% RH (no condensation)



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

