



## Panel Printer

# XP-MP801C



- MAX 160 mm/s , low noise and high speed printing.
- Supporting printing density adjustment.
- Supporting IAP online upgrade.
- Supports QRcode & PDF417 barcode system.



# XP-MP801C

## Panel Printer



Printing	
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm
Column capacity	576 dots/line
Printing speed	160 mm/s
Interface	USB+Serial+Parallel
Line spacing	3.75mm
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)

Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	32 Kbytes
NV Flash	64 Kbytes

Power	
Power source input	DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics	
Weight	0.37 Kg
Dimensions	140*142*110.7mm (D×W×H)

Environmental Requirements	
Work environment	Temperature: 0~45°C humidity : RH 10 ~ 80%
Storage environment	Temperature: -10~60°C humidity: RH 10~90°C

Reliability	
Cutter life	1 million cuts
Printer head life	100 KM



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.poskeytech.com  
Email: overseas@xprinter.net

