

# Xprinter®


## Panel Printer

# XP-MP01



# XP-MP01

## Panel Printer



### Printing

Printing method	Direct thermal
Paper roll diameter	60mm
Column capacity	384 dots/line
Printing speed	90 mm/s
Interface	USB
Paper thickness	0.06-0.08 mm
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)

### Barcode Character

Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
---------	---

### Power

Power adaptor	DC 12V/2.6A
Cash drawer output	DC 12V/1A

### Physical characteristics

Weight	0.183 Kg
Dimensions	109×94×66mm (D×W×H)

### Environmental Requirements

Work environment	Temperature: 0~45°C humidity : RH 10 ~ 80%
Storage environment	Temperature: -10~60°C humidity: RH 10~90%

### Reliability

Printer head life	50 KM
-------------------	-------

### Key features

- Mini size, light and multi-functions
- Easy to operate and connect
- Fast speed, high quality and stylish appearance

### Applications



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

