



Xprinter®

Thermal Receipt Printer

XP-Q80C

- Small size and low power consumption
- Support prompt and error alarm function
- Support IAP online upgrade
- Support Linux system and OPOS driver



XP-Q80C
Thermal Receipt Printer



Model	XP-Q80C	
Printing method	Direct thermal	
Media width	79.5±0.5mm / ϕ 80 mm	
Print width	72mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	200 mm/s	
Interface	USB / USB+Serial (Optional:USB+Bluetooth / USB+WiFi)	Lan (Optional: USB+Lan)
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	/	QR CODE
Input buffer	64 Kbytes	256 Kbytes
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100~240V, 50 ~ 60Hz	
Printer Input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	0.78 Kg	
Dimensions	166*126.5*128mm(D*W*H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)	
Reliability		
Auto cutter	Partial	
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows/ Linux/ macOS/ Android	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

