



Xprinter®

Thermal Barcode Printer



XP-Q302F

- Wall mount available
- 203 dpi resolution models
- Head-up sensor
- Support QR CODE, PDF417 printing
- Support IAP online update



XP-Q302F

Thermal Barcode Printer



Model		XP-Q302F	
Print mode	Label print mode	Receipt print mode	
Resolution	203 DPI	576 dots/line or 512 dots/line	
Printing method	Direct Thermal		
Max.print speed	127 mm/s	220 mm/s	
Max.print width	76 mm	72mm	
Media			
Media type	Thermal roll paper, thermal adhesive paper		
Media width	20mm ~ 80mm	//	
Media thickness	0.06 ~ 0.19 mm	0.06 ~ 0.08 mm	
Media roll diameter	Max.82 mm		
Paper taken method	Tearing off		
Performance Features			
Ram	4M		
Flash	4M		
Interfaces	USB+Serial+Lan; (Optional:USB+Serial+Lan+Bluetooth / WiFi)		
Sensors	Print head temperature sensor/ Paper end/ Cover open / Gap		
Fonts/Graphics/Symbologies			
1D barcode	CODE128 / 128M / EAN128 / CODE39 / 39C / 39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / 25 / 25C / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPC-E / UPCE+2 / UPC-E+5 / CPOST / MSI / MSIC / PLESSEY / ITF14 / EAN14	UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128	
2D bar code	PDF417、QRCODE、DataMatrix	PDF417、QR code	
Character sizes	FONT 1 to FONT 8 、K、TST24.BF2、TSS24.BF2	Font A:1.5mm×3.0mm(12×24 dots) Font B:1.1mm×2.1mm(9×17 dots) Chinese:3.0mm×3.0mm(24×24 dots)	
Emulation	TSC		
Physical Features			
Dimension	184.2×134.5×125mm (D×W×H)		
Weight	1.09 kg		
Reliability			
Print head life	50 km		
Software			
Driver	Windows		
SDK	iOS/ Android/ Windows		
Power supply			
Input	DC 24V/2.5A		
Environmental Conditions			
Operation	5 ~ 45℃, Humidity: 20 ~ 80%		
Storage environment	-40 ~ 55℃, Humidity: 93% (40℃)		



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

