

Xprinter®

TS-80F

Kiosk Printer



Key features


- Support QR CODE, PDF417 Printing
- Support multiple 1D code printing
- Support Linux/Windows system
- Support 256K bytes NV logo download printing

Applications



TS-80F

Kiosk Printer



Model	TS-80F
Printing method	Direct thermal
Printing speed	160 mm/s
Paper width	79.5 ± 0.5mm
Printing width	72mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line
Line space	3.75mm(changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	1D: UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128 2D: QR CODE / PDF417
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)
NV FLASH	4M Bytes
Input buffer	256Kbytes
Power supply	DC 24V / 2.5A
Cash drawer control	DC 24V / 1A
Interface	USB+Serial / USB+Parallel
Auto cutter	Partial
Reliability	Printing head life: 100 km; Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80RH%)
Storage environment	Temperature (-10~60°C), humidity(10~90RH%)
Drivers	WINDOWS / Linux / Android / IOS
Command	ESC/POS
Gross weight	1.8 kg
Dimension	202.7 × 158 × 140mm (D × W × H)



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

