



Thermal Receipt Printer

XP-Q833L

- 230, 260mm/s low noise, high speed printing
- Small size and low power consumption
- Support wall hanging function
- Support queuing function
- Support IAP online upgrade



XP-Q833L
Thermal Receipt Printer



Model	XP-Q833L	
Printing method	Direct thermal	
Media width	79.5±0.5mm / ϕ 80 mm	
Print width	72mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	230 mm/s	260 mm/s
Interface	USB / USB+Serial / USB+Lan /	USB+Serial+Lan
	(Optional: Bluetooth/Wifi)	(Optional: Bluetooth/Wifi)
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)	

Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE: Lan / USB+Lan	QR CODE / PDF417
Input buffer	128 Kbytes: USB+Serial / USB / USB+Bluetooth/USB+WiFi	
	256 Kbytes: Lan / USB+Lan / USB+Serial+Lan	
NV Flash	256 Kbytes	

Power	
Power adaptor	Input: AC 100~240V, 50 ~ 60Hz, Output: DC 24V/2.5A
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A

Physical characteristics	
Weight	0.87 Kg
Dimensions	180*145*130mm(D*W*H)

Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)

Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150Km

Software	
Emulation	ESC/POS
Driver	Windows / Linux / Mac OS / Android



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3932978
Http://www.xprintertech.com
Email: overseas@xprinter.net

