

Xprinter®

# Cloud Printing



PC, Ipad, Mobile



GPRS



WIFI



## XP-58IIQ

Thermal Receipt Printer

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver&Chinese Gb18030
- Compatible with ESC/POS commands

### APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

# XP-58IIQ

## Direct thermal Printer



|                                   |                                                                                       |
|-----------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>                      | <b>XP-58IIQ</b>                                                                       |
| <b>Printing method</b>            | Direct thermal                                                                        |
| <b>Paper width</b>                | 57.5±0.5mm                                                                            |
| <b>Print width</b>                | 48 mm                                                                                 |
| <b>Column capacity</b>            | 384 dots/line(Adjustable by command)                                                  |
| <b>Printing speed</b>             | 90 mm/s Max.                                                                          |
| <b>Interface</b>                  | USB+4G / USB+WIFI+4G / USB+Lan+4G / USB+Lan+WIFI                                      |
| <b>Line spacing</b>               | 3.75mm (Adjustable by commands)                                                       |
| <b>Roll diameter</b>              | 50mm                                                                                  |
| <b>Fonts Symbology</b>            |                                                                                       |
| <b>Character size</b>             | Afont A: 12x24, Font B: 9x17, CHN: 24*24                                              |
| <b>Characters /Line</b>           | Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets                              |
| <b>1D Barcode</b>                 | UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 |
| <b>2D Barcode</b>                 | QR code                                                                               |
| <b>Input buffer</b>               | 32 Kbytes                                                                             |
| <b>NV Flash</b>                   | 64 Kbytes                                                                             |
| <b>Power</b>                      |                                                                                       |
| <b>Power adaptor</b>              | AC 110V/220V, 50 ~ 60Hz12VDC, 2.6A                                                    |
| <b>Power source</b>               | DC 12V/2.6A                                                                           |
| <b>Cash drawer</b>                | DC 12V/1A                                                                             |
| <b>Physical characteristics</b>   |                                                                                       |
| <b>Weight</b>                     | 0.412kg                                                                               |
| <b>Dimensions</b>                 | 148*108*115mm (D×W×H)                                                                 |
| <b>Environmental Requirements</b> |                                                                                       |
| <b>Work environment</b>           | Temperature (0 ~ 45°C) humidity(10 ~ 80%)                                             |
| <b>Storage environment</b>        | Temperature(-10 ~ 60°C) humidity(10 ~ 90%)                                            |
| <b>Reliability</b>                |                                                                                       |
| <b>Printer head life</b>          | 50Km                                                                                  |
| <b>Software</b>                   |                                                                                       |
| <b>Emulation</b>                  | ESC/POS                                                                               |
| <b>Driver</b>                     | Windows/JPOS/Linux/Android/Mac                                                        |
| <b>Utility</b>                    | Windows & Linux test Utility                                                          |
| <b>SDK</b>                        | iOS, Android, Windows                                                                 |



Scan QR code to checkout Xprinter website for more update information.  
 Phone: (+86 756) 3895 852  
[Http://www.xprintertech.com](http://www.xprintertech.com)  
 Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

