


XP-Q371U

Thermal Barcode Printer

Xprinter®

XP-Q371U

Thermal Barcode Printer



| Model | | XP-Q371U |
|----------------------------------|---|--------------------|
| Print mode | Label print mode | Receipt print mode |
| Printing method | Direct Thermal | |
| Resolution | 203 DPI | |
| Max.print speed | 127 mm/s Max. | 180 mm/s |
| Max.print width | 76 mm | |
| RAM | 4M | |
| Flash | 4M | |
| Interfaces | USB / USB+Lan / USB+Serial+Lan (Optional: WiFi / Bluetooth) | |
| Print head temperature detection | Thermistor | |
| Print head position detection | Micro Switch | |
| Media | | |
| Media type | Thermal roll paper, thermal adhesive paper | |
| Media width | 20~80mm | |
| Media roll diameter | Max.83 mm | |
| Media inner diameter | 25mm~38mm | |
| Paper exit method | Tearing off | |
| Media thickness | 0.06 ~ 0.19 mm | |
| Fonts/Graphics/Symbologies | | |
| 1D barcode | CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14 | |
| 2D bar code | PDF417、QRCODE、DataMatrix | |
| Character sizes | Commonly used in single-byte fonts; FONT 1 to FONT 8, K, TST24.BF2,TSS24.BF2 | |
| Emulation | TSPL | ESC / POS |
| Physical Features | | |
| Dimension | 183*140*132.5mm | |
| Weight | 0.9 kg | |
| Operation | 5~45 °C, Humidity:RH 10 ~ 80% | |
| Storage environment | -40 ~ 55 °C, Humidity:93% RH | |
| Power Input | DC 24V/2.5A | |
| Print head life | 50 KM | |
| Operating system | WINDOWS/ Android / IOS | |



• Support both receipt printing and label printing



• Support missing paper alarm function



• Support IAP online upgrade



• Multiple interface,
USB / USB+Lan / USB+Serial+Lan
(Optional: WIFI / Bluetooth)



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

