

Xprinter®


Mobile Receipt Printer

XP-P503A



XP-P503A

Mobile receipt printer



Printing Features

Printing method	Direct thermal
Paper width	58mm
Line spacing	3.75mm (Adjustable by commands)
Print width	48 mm
Max.print speed	Max. 70 mm/s

Performance Features

Interfaces	USB+Bluetooth(1+1)
Printhead life	50 KM
CPU storage	128 Kbytes
NV Flash	4M bytes
Emulation	ESC/POS

Fonts/Graphics/Symbologies

Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm(9×17 dots) simplified/traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode types	1D: UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/ CODE93/CODE128 2D: QR CODE / PDF417
Extended character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/ Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/Arabic/ PT151(1251)
Rotation	0°、90°、180°、270°

Physical characteristics

Dimensions	125.49*90.39*58.57mm (L*W*H)
Gross weight	0.243kg

Compatible systems

Systems	Windows / Linux / Android / iOS
---------	---------------------------------

Power supply

Battery	3.7V / 2600mAh
Charging input	DC 5V / 1A

Environmental Conditions

Work environment	0 ~ 45°C, 10 ~ 80%RH no condensing
Storage environment	-10 ~ 60 °C, ≤10~90% RH no condensing

Key features

- Multiple 1D barcode printing
- QR CODE/PDF 417 2D barcode printing
- NV LOGO download picture printing
- Compatible with Windows/Linux/Android/iOS systems
- Multiple languages available.

Applications



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

