

XP-G480B

Industrial Thermal Transfer Label Printer



XP-G480B

Industrial Label Thermal Printer



- Label printer for industrial machine
- Network interface, flexible operation, large capacity, visual window



203DPI
200mm/s

300DPI
152mm/s


- Visual operation interface



- Visual perspective window



- Ribbon capacity 600M long



- 128MB Flash Memory/
128MB SDRAM



1. Plastic frame
2. Transparent cover design
3. Menu 4. Ribbon roller
5. Label roller 6. Print head



Model	XP-G480B	XP-G480E
Resolution	203 DPI	300 DPI
Print method	Thermal Transfer / Direct Thermal	
Max.Print speed	200 mm (8") / s Max.	152 mm (6") / s Max.
Max.print width	108 mm (4.25")	106mm (4.17")
Max.print length	2286 mm (90")	889 mm (35")
Media		
Media type	Continuous, gap, black mark, fan-fold and punched hole	
Media width	20 ~ 120 mm (0.78" ~ 4.7")	
Media thickness	0.06 ~ 0.254 mm (2.36 ~ 10 mil)	
Label length	10 ~2286 mm(0.39" ~ 90")	10 ~ 889 mm(0.39" ~ 35")
Media core diameter	203 mm (8")	
Ribbon	127 mm (5") OD (outside wound)	
Ribbon capacity	600 M	
Ribbon width	110 mm	
Performance Features		
Processor	32-bit CPU	
Memory	128MB Flash Memory/ 128MB SDRAM/ Flash memory can be expanded Max.4Gb	
Interface	USB / Serial / Lan Optional: Parallel/WIFI/TF card/Bluetooth	
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor	
Fonts/Graphics/Symbologies		
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.	
1D barcode	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11	
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Rotation	0°、 90°、 180°、 270°	
Emulaion	TSPL、 EPL、 ZPL、 DPL	
Physical Features		
Dimension	504 mm (D) x 257 mm (W) x 297 mm (H)	
Weight	10.22 kg	
Power supply		
Input	AC 100-240V, 50-60Hz	
Output	DC 24V / 2.5A, 60W	
Options		
Factory Options	①RS-232C (2400-115200 bps) communication interface; ②Ethernet server(10/100 Mbps); ③WiFi module ④Bluetooth module ⑤Paralled ⑥Peel ⑦Cutter	
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder	
Environmental Conditions		
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing	
Storage environment	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

