



Thermal Transfer / Direct Thermal

XP-TT435B


- Faster printing speed, 6 inches 127mm/s, to improve the daily efficiency.
- A new generation printhead is applied to enhance the printing quality.
- 300m ribbon capacity design.
- 8MB SDRAM & 8MB Flash memory for a more flexible usage.
- Rich emulation language compatibility: TSPL, ZPL, EPL, DPL.



Xprinter®

XP-TT435B

Thermal Transfer/ Direct Thermal



Printing Features		XP-TT435B
Resolution	300 DPI	
Print method	Thermal Transfer / Direct Thermal	
Max.Print speed	127 mm (5") / s	
Max.print width	104 mm (4.09")	
Max.print length	889 mm(35")	
Media		
Media type	Continuous, gap, black mark, fan-fold and punched hole	
Media width	25.4~118mm (1.0"~4.6")	
Media thickness	0.06~0.254 mm (2.36~10mil)	
Media core diameter	25.4 ~ 76.2 mm (1 " ~ 3 ")	
Label length	10 mm ~889 mm(0.39" ~ 35")	
Performance Features		
Processor	32-bit CPU	
Memory	8MB Flash Memory, 8MB SDRAM, Micro TF card reader for flash memory expansion, up to 4GB	
Interface	Standard version: USB Optional: Serial/Lan/WIFI/Bluetooth/TF card	
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor	
Fonts/Graphics/Symbologies		
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.	
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11	
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Rotation	0°、90°、180°、270°	
Emulaion	TSPL、EPL、ZPL、DPL	
Physical Features		
Dimension	302.5*234*195.18mm(D*W*H)	
Weight	2.66 kg	
Reliability		
Warranty	One year	
Print head life	30 km or first arrival first	
Options		
Factory Options	① LAN ② Serial ③ WIFI ④ Cutter ⑤ Bluetooth	
Dealer Options	① External paper roll holder and 1" paper roll; ② Extension board for external paper roll holder	
Environmental Conditions		
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing	
Storage environment	-40 ~ 60°C(-40~140°F), Humidity: 10 ~ 90% non-condensing	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

