




Xprinter®

XP-P816

Mobile Thermal Receipt Printer



Mobile Thermal Receipt Printer

XP-P816

- OLED screen, easy to operate
- Default 60 minute automatic shutdown
- Support receipt printing
- 2550mAh large capacity battery, long standby



Model		XP-P816
Printing method	Direct thermal	
Resolution	203 DPI	
Print width	104 mm	
Paper width	112mm	
Print speed	90 mm/s	
Media roll diameter	Max. 50 mm	
Performance Features		
Interfaces	USB+Bluetooth	
Memory	2176 Kbytes	
Input buffer	1024 Kbytes	
NV Flash	512 Kbytes	
Screen	1.3"OLED	
Emulation	ESC/POS	
Fonts/Graphics/Symbologies		
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) simplified/traditional Chinese: 3.0×3.0mm (24×24 dots)	
Barcode types	1D: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/ CODE128 2D: QRCODE/PDF417/DataMatrix	
Rotation	0°、90°、180°、270°	
Physical characteristics		
Gross weight	150 mm (L) x 131 mm (W) x 64 mm (H)	
Dimensions	0.56 kg	
Printer head life	50 KM	
Compatible systems		
Systems	Windows / Android / iOS	
Power supply		
Battery	7.4V/ 2550mAh, Adapter Input: DC 5V/ 2A	
Charging duration	Continuous printing for 1.6 hours (about 220m)	
Standby duration	3 hours	
Charging input	230 hours	
Environmental Conditions		
Work environment	10 ~ 40℃, 25 ~ 80%RH no condensing	
Storage environment	-40 ~ 60 °C, ≤10~90% RH no condensing	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3932 978
Http://www.xprintertech.com
Email: overseas@xprinter.net

