

# Xprinter®

## XP-TT426B

Thermal Transfer / Direct Thermal



Thermal Transfer / Direct Thermal

## XP-TT426B



- Equipped dual motor
- Print speed up to 127mm/s
- Ribbon roll capacity 300m, 25.4mm Ribbon Roller (Outer roll ribbon)
- Supporting TSPL-EZ printer language, Eltron and Zebra commands
- Large visual windows



<b>Model</b>	XP-TT426B
<b>Resolution</b>	203 DPI
<b>Print method</b>	Thermal Transfer / Direct Thermal
<b>Print speed</b>	127 mm (5") / s
<b>Max.print width</b>	104mm (4.09")
<b>Max.print length</b>	1778 mm (70")

<b>Media</b>	
<b>Media type</b>	Continuous, gap, black mark, fan-fold and punched hole
<b>Media width</b>	25.4-118mm (1.0"-4.6")
<b>Media thickness</b>	0.06~0.254 mm (2.36~10mil)
<b>Media core diameter</b>	25.4 ~ 76.2 mm (1" ~ 3")
<b>Label length</b>	10 - 1778 mm(0.39" ~ 70")
<b>Label roll capacity</b>	127 mm (5") OD (External Diameter)
<b>Ribbon capacity</b>	Max.300m
<b>Ribbon width</b>	110 mm
<b>Ribbon core inner diameter</b>	25.4 mm (1")

<b>Performance Features</b>	
<b>Processor</b>	32-bit CPU
<b>Memory</b>	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
<b>Interface</b>	USB (Optional:Lan/WIFI/Bluetooth/TF card)
<b>Sensors</b>	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor

<b>Fonts/Graphics/Symbologies</b>	
<b>Internal fonts</b>	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
<b>1D barcode</b>	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
<b>2D barcode</b>	PDF-417, Maxicode, DataMatrix, QR code, Aztec
<b>Rotation</b>	0°, 90°, 180°, 270°
<b>Emulation</b>	TSPL, EPL, ZPL, DPL

<b>Physical Features</b>	
<b>Dimension</b>	299 mm (D) x 235 mm (W) x 198.3 mm (H)
<b>Weight</b>	2.55 kg

<b>Reliability</b>	
<b>Print head life</b>	30 km

<b>Software</b>	
<b>Driver</b>	Windows / Linux / Mac
<b>SDK</b>	Windows / iOS / Android

<b>Power supply</b>	
<b>Input</b>	AC 110-240V,1.8A, 50-60Hz
<b>Output</b>	DC 24V, 2.5A, 60W

<b>Options</b>	
<b>Factory Options</b>	① Built-in Ethernet server (10/100 Mbps); ② RS-232C (2400-115200 bps) communication interface; ③ Cutter ④ Peeling machine ⑤ Bluetooth module ⑥ WiFi module
<b>Dealer Options</b>	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder

<b>Environmental Conditions</b>	
<b>Operation</b>	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
<b>Storage environment</b>	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 393 2978  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

