


Xprinter®

Mobile Label Printer

XP-P322B



Key features

- Support direct USB charging;
- 50mm diameter paper roll
- OLED screen available;
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-P322B

Mobile Label Printer



Printing	XP-P322B
Resolution	203 DPI
Printing method	Direct Thermal
Print speed	70mm (2.7") / s
Print width	72 mm (2.8")
Print length	1778 mm (70")

Media	
Media type	Continuous, gap, black mark
Media width	25.4 mm ~ 76 mm
Media thickness	0.06 mm ~0.16 mm

Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	Standard version: USB+Bluetooth Optional:USB+WIFI
Screen	OLED (0.96") Resolution:128*64 pix
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor

Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulaion	TSPL、EPL、ZPL、DPL、CPCL、ESC/POS

Physical Features	
Dimensions	120×112×60mm (D×W×H)
Weight	400 g

Reliability	
Printer head life	30Km

Software	
Operation system	Windows / Android / iOS
SDK	Windows / Android / iOS

Power supply	
USB	DC 5V/2A
Battery	2500mAh

Environmental Conditions	
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

