



Thermal Transfer/ Direct Thermal


XP-TT424B/TT434B

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon core inner diameter: 0.5"
- Bartender special edition



XP-TT424B / TT434B

Thermal Transfer/Direct Thermal Printer



Printer Specifications	XP-TT424B	XP-TT434B
Resolution	203DPI	300DPI
Print Method	Thermal Transfer / Direct Thermal	Thermal Transfer / Direct Thermal
Memory	8 MB RAM/8 MB Flash	8 MB RAM/8 MB Flash
Max. Print width	4.09 in.104 mm	4.25 in/108 mm
Max. Print Speed	Up to 5 ips (127 mm/s)	Up to 4 ips (102 mm/s)
Media Sensors	Movable Black Mark Sensor/Fixed Gap Sensor	
Emulation	TSPL, ZPL, EPL, DPL	
Interface	USB, USB+Ethernet(Optional Wireless Connectivity: Bluetooth / Wi-Fi)	
Others	Optional RTC, Optional SD Card Slot	

Media and Ribbon Characteristics		
Media Length	0.39 in.-70 in.(10 mm-1778 mm)	0.39 in.-35 in.(10 mm-889 mm)
Media Width	1 in.-3.3 in.(25.4 mm-84 mm)	
Media Roll Size	5 in./127 mm Outer Diameter/Core Inner Diameter: 1 in.(25.4 mm)	
Thickness	0.0023 in.(0.06 mm) Min.; 0.01 in. (0.254 mm) Max.	
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media	
Ribbon Outside Diameter	2.63 in./67 mm	
Max. Ribbon Length	90 meters	
Ribbon Width	1 in.-4.3 in.(25.4 mm-110 mm)	
Ribbon Core I.D.	1 in./25.4 mm	

Environment Condition	
Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Fonts/Graphics/Symbologies	
1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8

Software	
Driver	Windows / Linux / Mac / Android / Chrome OS
SDK	Windows / Linux / Android / iOS
Software	Bartender UltraLite / Mobile Label Design App

Accessories	
Standard Accessories	Power Adapter, Power Cord, USB Cable, User Manual, CD, Label spindle, Fixing tab, Ribbon spindle, Ribbon for test, Ribbon paper core, label roll for test
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Peel-off Module, Cutter Module
User Options	8" External Paper Roll Holder

Product Warranty	
Printhead life	The earlier of 30 km usage or 1 year
Platen roller life	The earlier of 30 km usage or 1 year
Printer Warranty	1 Year

Physical Characteristics	
Dimension	246 mm x 199 mm x 168 mm (D x W x H)
Weight	1.62 kg



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

