


Portable Thermal Printer

TP6

Xprinter®

TP6

Portable Thermal Printer



Model	TP6
Resolutions	300 DPI
Print method	Direct thermal
Max.Print width	48 mm
Printing speed	10 mm/s
Media Type	Continuous thermal paper, gap thermal paper(≥8mm)
Paper roll diameter	30 mm
Media width	58 mm
Media thickness	60~150μm
Sensor	Paper detection sensor; Cover open sensor;Overheat detection
Dimensions	86*86*41 mm (D*W*H)
Weight	0.16 kg
Peeling mode	Manual tearing off
Printer head life	50 KM
Battery	3.7V / 1000mAh, Standby time: 21.7 H; Full charge time:3.6H
Charge	5V / 1A
Interfaces	USB+Bluetooth
Memory	16 KB
Flash	128 KB
Operations	1 button, 1 indicator light
Environment	Temperature 5 ~ 40°C, humidity(25 ~ 85%) Temperature -40 ~ 60°C, humidity(10 ~ 90%)
Certification	FCC, CE, CB, CCC
Accessories	USB cable, Manual

Key features

- Low noise & Smooth printing
- Capable of 30mm diameter paper roll
- Compact & Portable
- Long standby time

Applications



Office



Pharmacy



Police



Transportation



School



POST



Scan QR code to checkout Xprinter
website for more update information.
Phone: (+86 756) 3932 978
Http://www.xprintertech.com
Email: overseas@xprinter.net

