



Xprinter®

Thermal Receipt Printer

XP-Q809K

- Multiple interface connections, wall mountable.
- Support QR code and PDF417.
- Compatible with ESC/POS commands.
- Support Windows, Linux, Android, IOS, OPOS, and MacOS.
- Support IAP online upgrade.



XP-Q809K

Thermal Receipt Printer



Model		XP-Q809K	
Resolution	203 DPI		
Printing method	Direct thermal		
Paper width	79.5±0.5mm		
Print width	72mm		
Column capacity	576 dots/line		
Printing speed	260 mm/s		
Interface	USB+Lan(USB+Lan+BT/WiFi)	USB+Serial+Lan (USB+Serial+Lan+BT/WiFi)	
Line spacing	3.75mm (Adjustable by commands)		
Paper type	Continuous paper		
Paper thickness	0.06mm-0.08mm		
Paper width	80mm		
Paper roll outer diameter	80mm±0.5mm		
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)		
Barcode Character			
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew /East Europe/ Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)		
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417		
Input buffer	4096 Kbytes		
NV Flash	256 Kbytes		
Power			
Power adaptor	Input: AC 100~240V, 50 ~ 60Hz		
Printer Input	DC 24V/2.5A		
Cash drawer	DC 24V/1A		
Physical characteristics			
Weight	0.84 Kg		
Dimensions	152 × 134 × 125mm(D*W*H)		
Environmental Requirements			
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)		
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)		
Reliability			
Auto cutter	Partial		
Cutter life	1.5 million cuts		
Printhead life	150 km		
Software			
Emulation	ESC/POS		
Driver	Windows / Linux / Mac OS / Android		



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3932978
Http://www.xprintertech.com
Email: overseas@xprinter.net

