

XP-TT425B


Thermal Transfer/ Direct Thermal Barcode Printer



Large capacity paper loading design



Black mark label



- **Multi-type media**, compatible with all types of label




- Support media width of **25.4 ~ 118mm**



- **5 inch large capacity**, **300m** ribbon capacity



- **152mm/s** printing speed




- Compatible with **TSPL / EPL / ZPL / DPL**



- Interface **USB**

XP-TT425B

Thermal Transfer /Direct Thermal Barcode Printer



Printer Specifications

Resolution	203DPI
Print Method	Thermal Transfer / Direct Thermal
Memory	8 MB RAM/8 MB Flash
Max. Print width	4.09 in./104 mm
Max. Print Speed	Up to 6 ips (152 mm/s)
Media Sensors	Movable Black Mark Sensor/Movable Gap Sensor
Emulation	TSPL, ZPL, EPL, DPL
Interface	USB, USB+Serial, USB+Ethernet, USB+Serial+Ethernet(Optional Wireless Connectivity: Bluetooth / Wi-Fi)
Others	Standard SD Card Slot, Optional RTC

Media and Ribbon Characteristics

Media Length	0.39 in.-70 in.(10 mm-1778 mm)
Media Width	1 in.-4.6 in.(25.4 mm-118 mm)
Media Roll Size	5 in./127 mm Outer Diameter/Core Inner Diameter: 1 in.(25.4 mm)
Thickness	0.0023 in.(0.06 mm) Min.; 0.01 in.(0.254 mm) Max.
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media
Ribbon Outside Diameter	2.63 in./67 mm
Max. Ribbon Length	300 Meters (984 ft.)
Ribbon Width	1 in.-4.3 in.(25.4 mm-110 mm)
Ribbon Core I.D.	1 in./25.4 mm

Environment Condition

Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Fonts/Graphics/Symbologies

1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8

Software

Driver	Windows / Linux / Mac / Android / Chrome OS
SDK	Windows / Linux / Android / iOS
Software	Bartender UltraLite / Mobile Label Design App

Accessories

Standard Accessories	Power Adapter, Power Cord, USB Cable, User Manual, CD, Label spindle, Fixing tab, Ribbon spindle, Ribbon for test, Ribbon paper core, label roll for test
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Peel-off Module, Cutter Module
User Options	8" External Paper Roll Holder

Product Warranty

Printhead life	The earlier of 30 km usage or 1 year
Platen roller life	The earlier of 30 km usage or 1 year
Printer Warranty	1 Year

Physical Characteristics

Dimension	302.5 mmx234 mm x 195.18 mm (D x W x H)
Weight	2.66 kg



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

