



## Thermal Receipt Printer

### XP-E200M / E260M / E300M

- Wall mount available;
- Apply easy load design to wireless interface card;
- Easy Maintenance: Takes 5S to update firmware only;
- User can search and manage Lan Printer directly by software;
- Steady performance: Resume from cutter jam error automatically.
- Excellent compatibility performance on different operating system.
- Energy control system to prevent printhead from overheating.



## XP-E200M / E260M / E300M Thermal Receipt Printer



| Model                      | XP-E200M                                                                                                                                                                                                                                                               | XP-E260M       | XP-E300M       |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------------|
| Printing method            | Direct thermal                                                                                                                                                                                                                                                         |                |                |
| Paper width                | 58mm / 80mm                                                                                                                                                                                                                                                            |                |                |
| Print width                | 72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm                                                                                                                                                                                                                                     |                |                |
| Column capacity            | 576 dots/line(adjustable by command)                                                                                                                                                                                                                                   |                |                |
| Printing speed             | 230 mm/s                                                                                                                                                                                                                                                               | 260 mm/s       | 300 mm/s       |
| Interface                  | USB/USB+Lan/USB+Serial                                                                                                                                                                                                                                                 | USB+Serial+Lan | USB+Serial+Lan |
| Line spacing               | 3.75mm(Adjustable by commands)                                                                                                                                                                                                                                         |                |                |
| Column number              | 80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/<br>Chinese, traditional Chinese - 21 columns or 24 columns                                                                                                                            |                |                |
| Character size             | ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)<br>Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)                                                                                                                                               |                |                |
| Cutter                     |                                                                                                                                                                                                                                                                        |                |                |
| Auto cutter                | Partial                                                                                                                                                                                                                                                                |                |                |
| Barcode Character          |                                                                                                                                                                                                                                                                        |                |                |
| Extension character sheet  | PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251) |                |                |
| Barcode types              | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128                                                                                                                                                                                                  |                |                |
| 2D Barcode                 | QR CODE / PDF417                                                                                                                                                                                                                                                       |                |                |
| Input buffer               | 128 Kbytes                                                                                                                                                                                                                                                             | 128 Kbytes     | 2048 Kbytes    |
| NV Flash                   | 256 Kbytes                                                                                                                                                                                                                                                             | 256 Kbytes     | 256 Kbytes     |
| Power                      |                                                                                                                                                                                                                                                                        |                |                |
| Power adaptor              | Input: AC 100-240V/50~60Hz;      Output: DC 24V/2.5A                                                                                                                                                                                                                   |                |                |
| Printer input              | DC 24V/2.5A                                                                                                                                                                                                                                                            |                |                |
| Cash drawer                | DC 24V/1A                                                                                                                                                                                                                                                              |                |                |
| Physical characteristics   |                                                                                                                                                                                                                                                                        |                |                |
| Weight                     | 1.16 Kg                                                                                                                                                                                                                                                                |                |                |
| Dimensions                 | 178×140×128mm (D×W×H)                                                                                                                                                                                                                                                  |                |                |
| Environmental Requirements |                                                                                                                                                                                                                                                                        |                |                |
| Operation environment      | Temperature (0 ~ 45℃) humidity(10 ~ 80%)                                                                                                                                                                                                                               |                |                |
| Storage environment        | Temperature(-10 ~ 60℃) humidity(10 ~ 90%)                                                                                                                                                                                                                              |                |                |
| Reliability                |                                                                                                                                                                                                                                                                        |                |                |
| Cutter life                | 1.5 million cuts                                                                                                                                                                                                                                                       |                |                |
| Printer head life          | 150 KM                                                                                                                                                                                                                                                                 |                |                |
| Software                   |                                                                                                                                                                                                                                                                        |                |                |
| Emulation                  | ESC/POS                                                                                                                                                                                                                                                                |                |                |
| Driver                     | Windows/JPOS/ OPOS/Linux/Android/Mac                                                                                                                                                                                                                                   |                |                |
| Utility                    | Windows & Linux test Utility                                                                                                                                                                                                                                           |                |                |
| SDK                        | iOS/Android/Windows                                                                                                                                                                                                                                                    |                |                |



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 393 2978  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

