

XP-T454B

Thermal Transfer / Direct Thermal


Xprinter®

XP-T454B


Thermal Transfer / Direct Thermal



- Use virtually any media for greater flexibility across a variety of use cases.



- 104mm(108mm) ultra wide Print specifications



- 5 Inch media OD capacity design



- Automatic cutter (optional)



- 300 meter (984') ribbon, 152mm/s print speed

- Reliable and quick printing
- Accurate print images
- Easy to operate
- Compact design
- Maximum quality standards



Printer Specifications	XP-T454B	XP-T454E
Resolution	203 DPI	300 DPI
Print Method	Thermal Transfer/ Direct Thermal	
Memory	32 MB SDRAM, 16 MB Flash (Optional: 64 MB SDRAM, 128 MB Flash)128 MB SDRAM, 256 MB Flash)	
Max. Print width	4.09 in./104 mm	4.25 in./108 mm
Max. Print Speed	Up to 6 ips (152 mm/s)	Up to 4 ips (102 mm/s)
Media Sensors	Movable Black Mark Sensor, Movable Gap Sensor	
Emulation	TSPL, ZPL, EPL, DPL	
Interface	USB, USB+Serial, USB+Lan, USB+Serial+Lan(Optional Wireless Connectivity: Bluetooth / Wi-Fi)	
Others	Standard SD Card Slot, Optional RTC	
Media and Ribbon Characteristics		
Media Length	0.39 in. - 1000 in. (10 mm - 25400 mm)	0.39 in. - 450 in. (10~11430 mm)
Media Width	0.78 in. - 4.7 in. (20 mm - 120 mm)	
Media Roll Size	5 in./127 mm Outer Diameter, Core Inner Diameter: 1 in. (25.4 mm)	
Thickness	0.0023 in.(0.06 mm) Min.; 0.01 in.(0.254 mm) Max.	
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media	
Ribbon Outside Diameter	2.63 in./67 mm	
Max. Ribbon Length	300 Meters (984 ft.) \ 110 Meters (360 ft.)	
Ribbon Width	1 in. - 4.3 in. (25.4 mm - 110 mm)	
Ribbon Core I.D.	0.5 in./12.7 mm, 1 in./ 25.4 mm	
Environment Condition		
Operating Temp.	5~40°C (41~104°F)	
Storage Temp.	-40~60°C (-40~140°F)	
Operating Humidity	25 ~ 85% Non-Condensing	
Storage Humidity	10 ~ 90% Non-Condensing	
Fonts/Graphics/Symbologies		
1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11	
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Fonts and Graphics	Font 0 ~ Font 8	
Software		
Driver	Windows / Linux / Mac / Android / Chrome OS	
SDK	Windows / Linux / Android / iOS	
Software	Bartender UltraLite / Mobile Label Design App	
Accessories		
Standard Accessories	Power Adapter, Power Cord, USB Cable, User Manual, CD, Label spindle, Fixing tab, Ribbon spindle, Ribbon for test, Ribbon paper core, label roll for test	
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Cutter Module	
User Options	8" External Paper Roll Holder	
Product Warranty		
Printhead life	The earlier of 30 km usage or 1 year	
Platen roller life	The earlier of 30 km usage or 1 year	
Printer Warranty	1 Year	
Physical Characteristics		
Dimension	276 × 215 mm x 188 mm (D x W x H)	
Weight	2.52 kg	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

