


XP-T261B/T261E

Thermal Transfer/ Direct Thermal

Xprinter®

XP-T261B/T261E
Direct Thermal Printer



- Preferred 2-inch barcode
- Suitable for various scenarios



Printer Specifications	XP-T261B	XP-T261E
Resolution	203 DPI	300 DPI
Print Method	Thermal Transfer / Direct Thermal	Thermal Transfer / Direct Thermal
Memory	8 MB RAM / 8 MB Flash	8 MB RAM / 8 MB Flash
Max. Print Width	2.2 in. / 56 mm	2.12 in./ 54 mm
Max. Print Speed	Up to 8 ips (203 mm/s)	Up to 6 ips (152 mm/s)
Media Sensors	Movable Black Mark Sensor / Fixed Gap Sensor	
Emulation	TSPL, ZPL, EPL, DPL	
Interface	USB, USB+Lan, Optional Wireless Connectivity: Bluetooth / Wi-Fi, Optional USB HOST	
Others	Standard RTC, Doesn't Support SD Card Slot	

Media and Ribbon Characteristics		
Media Length	0.39 in.~70 in. (10 mm ~ 1778 mm)	0.39 in.~35 in.(10~889mm)
Media Width	0.59 in. - 2.3 in. (15 mm - 60 mm)	
Media Roll Size	4 in./101.6 mm Outer Diameter, Core Inner Diameter: 1 in. (25.4 mm)	
Thickness	0.0023 in. (0.06 mm) Min.; 0.01 in. (0.254 mm) Max.	
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media	
Ribbon Outside Diameter	1.57 in./40 mm	
Max. Ribbon Length	110 Meters (360 ft.)	
Ribbon Width	1 in. - 2.3 in. (25.4 mm ~ 60 mm)	
Ribbon Core I.D.	0.5 in./12.7 mm	

Environment Condition	
Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Fonts/Graphics/Symbologies	
1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E,EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8

Software	
Driver	Windows / Linux / Mac / Android / Chrome OS
SDK	Windows / Linux / Android / iOS
Software	Bartender UltraLite / Mobile Label Design App

Accessories	
Standard Accessories	Power Adapter, Power Cord, USB Cable, User Manual, CD, Ribbon Spindle*2, Ribbon For Test, Ribbon Paper Core, Label Roll For Test
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Peel-off Module, Cutter Module
User Options	8" External Paper Roll Holder


Physical Characteristics	
Dimension	246 mm × 140 mm × 170 mm (D × W × H)
Weight	1.65 Kg



- Support printing with multiple materials




- Ribbon capacity 110m, half-inch core ribbon roll





203 DPI
203mm/s

- 203mm/s printing speed



- 127 mm (5") OD media capacity



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

