




# Xprinter®

## XP-76IIN

Impact Dot matrix Printer



Impact Dot matrix Printer

## XP-76IIN

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



Printing	XP-76IIN
Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5mm
Column capacity	400 dots/line
Max. print speed	4.5 line/s
Interface	USB / Parallel / Serial / Lan
Printing paper	75.5±0.5mm×φ80mm(max)
Line spacing	4.23mm (Adjustable by commands)
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	76mm paper: Font A - 32 columns /Font B - 42 columns / Chinese, traditional Chinese - 16 columns

Character	
Extension character sheet	PC437/Katakana/PC850/PC860/PC863/PC865/ WPC1252/PC866/PC852/PC858

Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics	
Weight	1.28KG
Dimensions	220×150×140mm (D×W×H)

Environmental Requirements	
Work environment	0 ~ 45°C, 10 ~ 80% RH
Storage environment	-10 ~ 60°C, 10 ~ 90% RH (no condensation)

Reliability	
Printer head life	10 Million Lines



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 393 2978  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

