

Portable Thermal Printer


Xprinter®

TP6



TP6

Portable Thermal Printer



Model	TP6
Resolutions	304 DPI
Print method	Direct thermal
Max.Print width	48 mm
Max. print speed	15 mm/s
Media Type	Continuous thermal paper, gap thermal paper
Paper roll diameter	30 mm
Media width	57 mm
Media thickness	60~150µm
Sensor	Paper detection sensor; Cover open sensor
Dimensions	86*86*40 mm (D*W*H)
Weight	0.165 kg
Peeling mode	Manual tearing off
Printer head life	50 KM
Battery	7.4V / 1000mAh, Standby time: 24.5H; Full charge time:1.5H
Charge	5V / 1A
Interfaces	USB+Bluetooth
Memory	16 KB
Flash	128 KB
Operations	1 button, 1 indicator light
Environment	Temperature 5 ~ 40°C, humidity(25 ~ 85%) Temperature -40 ~ 60°C, humidity(10 ~ 90%)
Certification	FCC, CE, CB, CCC
Accessories	USB cable, Manual

Key features

- Low noise & Smooth printing
- Capable of 30mm diameter paper roll
- Compact & Portable
- Long standby time

Applications



Office



Pharmacy



Police



Transportation



School



POST



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3932 978
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

